



## Palit GTX 560 Ti SONIC

- Palit Own Design GTX 560 Ti
- Sonic Overclocking Version
  - 9% higher than non-OCed
- Compact size
- Dual-Fan thermal solution



Product Photo

Product Name

GTX 560 Ti Sonic

VGA Chip

GTX 560 Ti

PN

NE5X56TS1102F  
NE5X56TS1102-1140F

Core Name

GF114

### Specifications

Process technology	40nm
Processor Cores	384cores
Memory Amount	1024MB
Memory Interface	256bit
DRAM Type	GDDR5
Graphics Clock	900MHz
Memory Clock	2100MHz (DDR 4200MHz)
Processor Clock	1800MHz
Memory Bandwidth	134.4 (GB/Sec)
Power Consumption	180W

### Output Support

HDMI, Dual DVI, VGA



### Accessory

Driver CD



Manual



Power Cable



### Key Features

- Microsoft DirectX11 support
- NVIDIA CUDA technology with CUDA C/C++
- DirectCompute 5.0 and OpenCL support
- NVIDIA PhysX technology
- NVIDIA SLI Ready
- NVIDIA 3D Vision Surround Ready\*
- NVIDIA PureVideo HD technology
- PCI Express 2.0 support
- Two dual-link DVI connectors
- One HDMI 1.4a connector
- Dual-link HDCP capable
- OpenGL 4.1 support



\* Require NVIDIA SLI configuration, 3D Vision Glasses and 3pcs 3D Vision ready displays.

### Minimum system requirements

Graphics card require:

- PCI Express or PCI Express 2.0-compliant motherboard with one dual-width x16 graphics slot
- Two 6-pin PCI Express supplementary power connector
- Minimum 500W or greater system power supply (with a minimum 12V current rating of 30A)
- Supported Operating Systems: Windows 7, Windows Vista, Windows XP

### Dimension

PCB: 188mm(L) x 112mm(W)  
Cooler :2 slot  
Bracket: 2 slot

Box: 342x221x66mm  
Retail Pack: 20 pcs per carton  
Bulk Pack: 20 pcs per carton